


Myjnie przejezdne tunelowe

Construction


Inner sheathing made of stainless steel





Pumps made of stainless steel

Zones separated by width-adjustable curtains




© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl



Easy access to the tanks from outside the car wash


Drip zones between processes





Angle profiled spray pipes

Modular construction





© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl



Insulated housing, made of easily removable panels

Bars for the operator to enter the car wash






Pre-filtration of each process

The width of the inlet to the car wash is regulated by sliding doors




© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl




Plastic interchangeable nozzles with adjustable spray angle

Benefits

Low liquid transfer






High washing accuracy

ROMER

© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl


Closed-circuit washing



Control


Intuitive 7"






Login for technologists and operators

Programming of cascade levels and scrubbing refresh




© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl



touch panel control Built-in car wash work calendar

Built-in calendar to monitor conductivity, pH of chemical treatments and washes



Modbus communication with other master controllers

Equipment

Filtration of the chemical treatment with a flow filter



© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl



Stepless measurement of the amount of liquid in each tank


Pipelines equipped with pressure gauges





Automatic cascade between processes - controlled by pneumatic valves

Direct heating with burner or electric heaters





© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl



Fume hoods along the entire length of the rail

Additional sealing under the rail





Flows on the pumps are regulated manually with butterfly valves, optionally with inverter inverters

© 2023 ROMER Skarżysko-Kamienna 26-110 ul. Rejowska 99A | www.romer.com.pl | kontakt@romer.com.pl